

## P series—Corning Gold Patch Cords

Fiber Connections Inc. is a Corning Cable Systems CAH Gold Program member. Gold Program members adhere to Corning recommended manufacturing practices and are subject to annual audits by Corning Cable Systems. Corning Gold patch cords and pigtails can be made with any standard fiber and connector type in both standard and custom lengths.



CAH Connections<sup>SM</sup>  
Gold Program



## Ordering Information

Fiber Type	
1	62.5/125 (OM1)
2	SM (OS2)
3	50/125 (OM2)
9	50/125 (OM3)
A	50/125 (OM4)
Z	Custom

Cable Rating	
R	Riser FT4
P	Plenum FT6
L	LSZH
T	PVC (for 900um)
Z	Custom

Assembly Performance	
E	EFG (Ref. Grade)
F	EFG (Ref. Grade) w/test data
L	Low Loss
M	Low Loss w/ test data
S	Standard Performance
T	Standard Performance w/test data
Z	Custom

Length in meters



Fiber Count	
1	1 Fiber
2	2 Fiber
Z	2 Fiber

Cable Design	
A	900um Tight Buffered
B	1.6mm Simplex
C	2mm Simplex
D	3mm Simplex
E	1.6mm Duplex
F	2mm Duplex
G	3mm Duplex
Z	Custom

Connector Types	
LC	LC Simplex
LD	LC Duplex
LU	LC Uniboot
LM	LC Mini
SC	SC Simplex
SD	SC Duplex
ST	ST
0	Pigtail /Unterminated
SA	SC/APC Simplex
SZ	SC/APC Duplex
FC	FC
FA	FC/APC
RM	MTRJ(m) Pinned
RJ	MTRJ(f) non-pinned
ZZ	Custom

Polarity	
F	Standard
G	Reversed
Z	Custom

Pull-kits	
0	None
1	1 installed
2	2 installed

## Specifications

### Connector Performance Specifications

Connector Type	Max Insertion Loss (dB)		Reflectance OS2 (dB)	Reflectance OMB/OM4 (dB)	Durability	Ferrule Material	Housing Material
	Low Loss / EFG Grade	Standard					
LC	0.2	0.4	≤ -55	-25	< 0.2dB	Ceramic	Composite
SC	0.2	0.4	≤ -55	-25	< 0.2dB	Ceramic	Composite
ST	0.2	0.4	≤ -55	-25	< 0.2dB	Ceramic	Metal Alloy
FC	0.2	0.4	≤ -55	-25	< 0.2dB	Ceramic	Metal Alloy
SCapc	0.2	0.4	≤ -65	-25	< 0.2dB	Ceramic	Composite
FCapc	0.2	0.4	≤ -65	-25	< 0.2dB	Ceramic	Metal Alloy
MTRJ	0.3	0.4	≤ -40	-25	< 0.2dB	Composite	Composite

### Fiber Performance Specifications

Fiber Type	Maximum Attenuation (DB/km)		Min Over Filled Launch (MHz•km)		Min. Effective Modal Bandwidth (MHz•km)		Serial 1 Gigabit Ethernet Distance (m)		Serial 10 Gigabit Ethernet Distance (m)	
	850nm	1300nm	850nm	1300nm	850nm	1300nm	850nm	1300nm	850nm	1300nm
OM1	3.4	1.0	200	500	220	-	300	550	33	-
OM2	3.0	1.0	700	500	950	-	750	600	150	-
OM3	3.0	1.0	1500	500	2000	-	1000	600	300	-
OM4	3.0	1.0	3500	500	4700	-	1100	600	550	-
	<b>1310nm</b>	<b>1550nm</b>	<b>1310nm</b>	<b>1550nm</b>	<b>1310nm</b>	<b>1550nm</b>	<b>1310nm</b>	<b>1550nm</b>	<b>1310nm</b>	<b>1550nm</b>
OS2	0.65	0.5	-	-	-	-	5000	-	10000	40000

Please contact customer service for additional information.

Custom configurations available upon request.

All specifications are subject to change

**CORNING**

**CAH Connections™  
Gold Program**