

Specifications

Connector Performance Specifications

Connector Type	Max Insertion Loss (dB)		Reflectance OS2 (dB)	Reflectance OM3/OM4 (dB)	Durability	Ferrule Material	Housing Material
	Low Loss / EFG Grade	Standard					
LC	0.2	0.4	≤ -55	-25	< 0.2dB	Ceramic	Composite
SC	0.2	0.4	≤ -55	-25	< 0.2dB	Ceramic	Composite
ST	0.2	0.4	≤ -55	-25	< 0.2dB	Ceramic	Metal Alloy
FC	0.2	0.4	≤ -55	-25	< 0.2dB	Ceramic	Metal Alloy
SCapc	0.2	0.4	≤ -65	-25	< 0.2dB	Ceramic	Composite
FCapc	0.2	0.4	≤ -65	-25	< 0.2dB	Ceramic	Metal Alloy
LCapc	0.2	0.4	≤ -65	-25	< 0.2dB	Ceramic	Metal Alloy
MTRJ	0.3	0.4	≤ -40	-25	< 0.2dB	Composite	Composite

Fiber Performance Specifications

Fiber Type	Maximum Attenuation (DB/km)		Min Over Filled Launch (MHz•km)		Min. Effective Modal Bandwidth (MHz•km)		Serial 1 Gigabit Ethernet Distance (m)		Serial 10 Gigabit Ethernet Distance (m)	
	850nm	1300nm	850nm	1300nm	850nm	1300nm	850nm	1300nm	850nm	1300nm
OM1	3.4	1.0	200	500	220	-	300	550	33	-
OM2	3.0	1.0	700	500	950	-	750	600	150	-
OM3	3.0	1.0	1500	500	2000	-	1000	600	300	-
OM4	3.0	1.0	3500	500	4700	-	1100	600	550	-
	1310nm	1550nm	1310nm	1550nm	1310nm	1550nm	1310nm	1550nm	1310nm	1550nm
OS2	0.65	0.5	-	-	-	-	5000	-	10000	40000

Please contact customer service for additional information.

Custom configurations available upon request.

All specifications are subject to change